





Owl Timeclock Pix 25[®]

A durable, small and easy-to-use Atomic Time Recorder/ Time and Date Stamp

- Large, easy to read digital display
- Accurate, real-time clock synchronization with atomic time functionality
- Easy to replace ribbon cartridge saves time
- Wall or desk mount provides for flexible operation

Request Quote

Owl Timeclock supports its customers through a network of regional offices and a central Customer Care Center.



PIX 25

The PIX-25 Electronic Time Recorder automatically synchronizes to the NIST (National Institute of Standards and Technology) Atomic Clock via wireless radio signals. The PIX-25 also

automatically adjusts for Daylight Savings Time while providing the bene ts of an economical payroll recorder and time & date stamp functionality.

Features

- Ability to synchronize to the atomic clock Ribbon ink capacity indicator
- Cartridge ribbon for easy change
- Atomic Clock Indicator
- · Quartz accuracy
- Configurable print direction for left or right hand printing
- Prints multiple languages and pre-con gured messages
- Automatically changes year, month and date

- Automatic or manual print
- Programmable print styles, military or regular time
- Prints in minutes, hundredth and tenths
- Internal perpetual calendar automatically adjusts for Daylight Saving Time, leap years and short months
- Clear printing on paper or time cards 3-year battery backup retains time, settings One Year Factory Warranty



Head Office: Toronto 310 Judson St., Unit 6, Toronto, Ontario M8Z 5T6 Tel: 416-252-1186 Toll Free: 1-877-567-0633

Owl Time Clock Pix 25[®]

Low Ink Sensor



Atomic Clock Sensor



Benefits

- Large, easy to read digital display
- Illuminated print window and guide improves e ciency on time card stamping
- Automatic or manual print activation ensures accurate registration
- Locking enclosure prevents tampering with settings and reduces time card fraud
- Accurate, real-time clock synchronization with atomic time functionality Easy to replace ribbon cartridge saves time
- Wall or desk mount provides for exible operation

Technical Specifications

Size

- 6.83 in. (155 mm) high
- 6.75 in. (175 mm.) deep

Weight:

• 3.9 lbs. (1.77 kg)

Power Adaptor:

• 100-240 VAC, 50/ 60Hz

Clock Input

• 15 VDC, 1.2A (Max)

Ambient Temperature:

• -10°C ~ 45oC (-14oF ~ 113oF)

Humidity:

• 10% ~ 90% (no condensation)



